

Vision 360

FRONT VIEWER CONFIGURATION



Viewer Setup:

You have to place all necessary folders (CSS, imaged, images, JavaScript) and vision360.html to same directory. (Directories structures should same as given sample project.)

Folder wise all data file must be place in “**imaged**”

folder. E.g.:

Imaged/movienam1/
Imaged/movienam2/

After folder setup you can use following configuration option for the viewer.

Sample code of Vision360.html

```
<html>
  <head>
    <meta http-equiv="Content-Type" content="text/html; charset=UTF-8" />
    <meta name="viewport" content="user-scalable=no" />
    <meta http-equiv="X-UA-Compatible" content="IE=Edge" />
    <title>Vision360 Viewer </title>
    <link href="css/vision360.css" rel="stylesheet" type="text/css" />
    <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.12.2/jquery.min.js" ></script>
    <script type="text/javascript" src="js/w.js"></script>
    <script type="text/javascript" src="js/vision360.js"></script>
    <script>
      $(document).ready(function(){
        $('.Vision360').Vision360();
      });
    </script>
  </head>
  <body>
    <div class='Vision360' ></div>
  </body>
</html>
```

Default Settings from html page

```
$('.Vision360').Vision360({
  movieName:"", //Movie Name
  surl: "", //Data file stored in different server
  autoPlay:1, // Pass 1 or 0 If you want to see auto play
  infoURL:"", //If Information get from other server or website
  zoom:1, //Pass 1 or 0 If you want to see zoom button
  buttons:"", //If you don't want to see navigation button then 0
  speed:0, //Set speed of viewer
  scaleRatio:'-10', // Used to increase and decrease the size of viewer
  watermarkPosition:7, // 1:Top Left ,3: Top Right, 7: Bottom left, 9: Bottom Right
  otherLogo:"", //Base64 image data
  otherLogoPosition:'1', // 1:Top Left ,3: Top Right, 7: Bottom left, 9: Bottom Right
  otherLogoLink:"
});
```

Open **Vision360.html** file in browser with HTTP or HTTPS URL only.

Query String Parameter Configurations:

Mandatory Query String Parameter:

1. d = Movie Name

- o This parameter is mandatory.
- o d = "Movie folder" (e.g. moviename1, moviename2) name placed in folder "imaged"
- o In case you pass "movieName" in setting then not need to pass in query string.

2. Example:

<http://www.v360.in/viewer4.0/vision360.html?d=moviename1>

where "moviename1" is **moviename1 is Data Directory Name** within the "imaged" directory where actual data file is stored.

Compare Mode

Compare Mode provides to compare more than two movies. You can compare more than two movies, by passing their Movie Name with comma separator.

o Example:

www.v360.in/viewer4.0/vision360.html?d=moviename1,moviename2

where "moviename1" and "moviename2" are **Movie Directory Name** within the "imaged" directory where actual data file are stored.

Optional Query String Parameters:

sm = Eye-Scan View

sm is used to display eye scan view, to display the eye scan view the value of **sm** should be **1**. If you don't pass the parameter, it will not show eye scan view.

Example :

Show Eye-Scan View

www.v360.in/viewer4.0/vision360.html?d=movienam&sm=1

Notes : Set Iframe width and height as per your requirement

sr = Scale Ratio

sr is used to increase and decrease the size of viewer. To decrease the size of the viewer value of **sr** should be from **-1** to **-100** and to increase the size of the viewer value of **sr** should be from **1** to **100**. If you don't pass the parameter, it will take **0**.

Example :

Scale ratio is -10

www.v360.in/viewer4.0/vision360.html?d=movienam&sr=-10

Scale ratio is 20

www.v360.in/viewer4.0/vision360.html?d=movienam&sr=20

esr = Eye Scale Ratio

esr is used to increase and decrease the size of eye scan viewer. To decrease the size of the eye scan viewer value of **esr** should be from **-1** to **-100** and to increase the size of the viewer value of **esr** should be from **1** to **100**. If you don't pass the parameter, it will take **0**.

Example :

Eye Scale Ratio =-10

www.v360.in/viewer4.0/vision360.html?d=movienam&sm=1&esr=-10

Eye Scale Ratio =20

www.v360.in/viewer4.0/vision360.html?d=movienam&sm=1&esr=20

s = Speed

s is used to increase and decrease the speed of rotation. To decrease the speed of rotation value of **s** should be from **1** to **200** and to increase the speed of rotation value of **s** should be from **-1** to **-200**. If you don't pass the parameter, it will take **0**.

Example :

speed is -10 -

www.v360.in/viewer4.0/vision360.html?d=movieName&s=-10

speed is 20

www.v360.in/viewer4.0/vision360.html?d=movieName&s=20

surl = URL of the Movie Data

surl is used when your movie data file stored in different server. Movie data file must be placed in "imaged" folder on that sever, "imaged" folder path should be provided to surl. If you don't pass the parameter, it will take path of local folder.

Example :

Path of the movie is

www.yourwebsiteurl.com/viewer4.0/vision360.html?d=movieName&surl=https://yourwebsiteurl.com/images/company/

i = Information

i is used when your movie information is displayed from other server. If you don't pass the parameter, it will take default value.

Example :

www.v360.in/viewer4.0/vision360.html?d=movieName&i=http://yourwebsitename.com/MovieDetail.aspx?d=movieName

Here, we are loading information from info URL (<https://v360.in/MovieDetail.aspx?d=movieName>)
Webpage Implementation : get movieName form URL and fetch data from database and design data in your way

You must write data between <div id="v360"> </div>, sample division and sample code are mention below

--Sample Division--

```
<div id="v360" style="custome style">
```

```
--put information in any format -
```

```
</div>
```

--Sample Code--

```
<div id='v360' style='margin:0; font-size:15px;letter-spacing: 1px;'>
```

```
<b>Diamond name: </b> 1 <br/><b>Shape : </b>Round <br/><b>Size: </b> 5
```

```
</div>
```

Note: .

- You can use any web technology for displaying stone information
- For .NET technology, please see attached "getinfo.aspx" page

z=Zoom

z is used to display zoom button. To show the zoom button, the value of **z** should be **1** and to hide the zoom button, the value of **z** should be **0**. If you don't pass the parameter, it will take **0**.

Example :

www.v360.in/viewer4.0/vision360.html?d=movieName&z=1

sp = Position of Eye-Scan View

sp is used to display eye scan view in different position on the screen. The position of the eye scan view can be top-left, top-right, bottom-left and bottom-right. To display the eye scan view in different position, following are the examples.

Example :

Top-Left

www.v360.in/viewer4.0/vision360.html?d=movieName&sm=1&sp=1

Top-Right

www.v360.in/viewer4.0/vision360.html?d=movieName&sm=1&sp=2

Bottom-Left

www.v360.in/viewer4.0/vision360.html?d=movieName&sm=1&sp=3

Bottom-Right

www.v360.in/viewer4.0/vision360.html?d=movieName&sm=1&sp=4

btn = button

btn is used when you show/hide the button of viewer. To hide all button value of **btn** should be **0**. If you don't pass the parameter, it will show all the buttons. If you show/hide the button randomly than following are the examples.

Example :

Hide all buttons

www.v360.in/viewer4.0/vision360.html?d=movieName&btn=0

Next and Previous

www.v360.in/viewer4.0/vision360.html?d=movieName&btn=1

Play

www.v360.in/viewer4.0/vision360.html?d=movieName&btn=2

Reverse

www.v360.in/viewer4.0/vision360.html?d=movieName&btn=3

Info

www.v360.in/viewer4.0/vision360.html?d=movieName&btn=4

To show buttons in combination Show next, previous and play buttons

www.v360.in/viewer4.0/vision360.html?d=movieName&btn=1,2

Show play and reverse buttons

www.v360.in/viewer4.0/vision360.html?d=movieName&btn=3,4

sd =Eye scan view distance from viewer

sd is used to change the distance between the main viewer and eye scan viewer, the value of **sd** should be from **50** to **250**. If you don't pass the parameter, it will take **100**.

Example :

Show distance from viewer

www.v360.in/viewer4.0/vision360.html?d=movieName&sm=1&sd=50

autoplay=Viewer auto play after mouse interaction

autoplay is used to auto play viewer after mouse interaction. To stop viewer after mouse interaction **autoplay** should be 0 and auto play viewer after mouse interaction **autoplay** should be **1**. If you don't pass the parameter, it will take **1**.

Example :

www.v360.in/viewer4.0/vision360.html?d=movieName&autoPlay=1

You can see viewer: **without Iframe and with Iframe.**

- ❖ To use viewer without iframe, simply open vision360.html and then pass parameter?d= movieName. So URL will be www.v360.in/viewer4.0/vision360.html?d=movieName
- ❖ To use Viewer with iframe then give your iframe src as vision360.html?d= movieName.
<iframe src="www.v360.in/viewer4.0/vision360.html?d=movieName" height="750" width="650" scrolling="no" frameborder="0" seamless="seamless"></iframe>